

Product information 0905 204 302/0,6 M

| Name | 0905 204 302/0,6 M |
|---------------------------------------|---|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| Delinear informations | Profibus power supply double, molded on both sides: with 7/8" male connector and 7/8" female connector, 5 poles, 0.6 m. |
| Delivery informations | availabla |
| Availability | available |
| Product description | 0905 204 302/0,6 M |
| Type Order No. | |
| | 84214 |
| Description | Profibus power supply double, molded on both sides: with 7/8" male connector and 7/8" female connector, 5 poles, 0.6 m. |
| Note | The application of these products in harsh environments should always be checked before use. |
| Color of housing | black |
| Product characteristics | Oil resistance |
| Classification | |
| Belden class | Power Supply Cable |
| Belden brand | Lumberg-Automation |
| Cable | laar. |
| Cable length | 0.6 m |
| Cable number | 204 |
| Cable description | Power supply cable |
| Color of jacket | black |
| Material of outer jacket | PUR |
| Without halogens as in EN 50267-2-3 | ✓ |
| shielded | × |
| welding spark proof | × |
| Outer diameter of the cable | 8 mm |
| Number of conductors | 5 |
| Cable design | 5 x 1.00 mm ² |
| Conductor design | 128 x 0.10 mm |
| Flame resistant according to standard | none |
| | |