

## **Product information** 0985 478 604/...M - 0985 478 604/1 M

| Name                                      | 0985 478 604/M   |
|---|--|
|   | U  |
|   | Cord set, double-ended, M12-RJ45, Industrial Ethernet Data cable for GigaBit Applications, molded with M12 male connector (X coded, 8 poles) and RJ45 connector, PUR jacket, halogen-free, black, 1 meter. |
| Delivery informations                     |  |
| Availability                              | available  |
| Product description                       |  |
| Туре                                      | 0985 478 604/1 M   |
| Order No.                                 | on request / auf Anfrage   |
| Description                               | Cord set, double-ended, M12-RJ45, Industrial Ethernet Data cable for GigaBit Applications, molded with M12 male connector (X coded, 8 poles) and RJ45  |
|   | connector, PUR jacket, halogen-free, black, 1 meter.   |
| Note                                      | Transmission properties for Cat 6 and Cat 6A compliant with IEC PAS 61076-2-109. The application of these products in harsh environments should always be checked before use.                              |
| Color of housing                          | black  |
| Number of contacts                        | 8  |
| Classification                            |  |
| Belden class                              | Industrial Ethernet Data Cables  |
| Belden brand                              | Lumberg-Automation   |
| Mechanical data                           |  |
| Type of plug-in contact                   | Male connector   |
| Type of plug-in contact, side 2           | Male connector   |
| Design of housing                         | straight   |
| Design of housing, side 2                 | straight   |
| Coding of the M12 round plug connector    | X  |
| Environmental conditions                  | ^  |
| Environmental temperature (explanation)   | -30°C 90°C (M12), -20°C 75°C (RJ45)  |
| Degree of protection (IP), mounted        | IP 67 (M12) / IP 20 (RJ45)   |
|   |  |
| Pollution degree<br>Materials             | 3  |
| Housing material / Molded body            | ТРИ  |
| Contact bearer material                   | PA (M12)   |
| Contact material                          | CuZn   |
| Contact material - Surface refinement     | gold-plated  |
| Contact material - Surface remember       | PC (RJ45)  |
|   |  |
| Knurled screw / nut material Approvals    | CuZn, nickel-plated  |
|   | lige   |
| RoHS 2002/95/EG compliant Electrical data | yes  |
| Insulation resistance                     | >1 6Ω  |
| Cable                                     |  |
| Cable length                              | 1 m  |
| Cable number                              | 478  |
| Cable description                         |  |
| Color of jacket                           | Bus cable  |
| · · · · · · · · · · · · · · · · · · ·     | black  |
| Material of outer jacket                  | PUR  |
| Without halogens as in EN 50267-2-3       | ✓  |