

EPIC® ULTRA H-A 3 TBF

Housing EPIC® ULTRA: for higher functional reliability

EPIC® Rectangular connector housing EMC protection, corrosion resistant, UL50E, Nema250

Info

EMC protection

Corrosion-resistant

Protection rating UL50E tested



Waterproof



Interference signals



Connector with standard housing unit



Robust



Space requirement

Benefits

Optimum, low-resistance 360° screening

All-purpose due to high corrosion resistance and high environmental protection.

Space-saving due to compact dimensions

High mechanical and chemical resistance

Application range

In EMC-sensitive environments

For fixed and flexible applications (e.g. machinery building, wind turbines)

Construction machinery

Electric motor manufacturing

EPIC® ULTRA H-A 3 TBF

Product features

Pluggable with standard housings

Resistance to cyclic salt spray is tested according to IEC 68-2-52, severity level 2

Salt spray testing according to DIN EN ISO 9227, method NSS, period of test 480 hours

Corrosion-resistant according to DIN EN 6988

Delivery including stainless steel screw for the inserts

Technical Data

| | |
|--------------------|--|
| Classification: | ETIM 5.0 Class-ID: EC000437 ETIM 5.0 Class-Description: Housing for industrial connectors |
| Material: | Housing: nickel-plated zinc diecasting Lever: stainless steel Sealing: NBR |
| Protection rating: | IP 65 NEMA 250, UL50E: 12, 4, 4X (latched) |
| Temperature range: | -40°C to +100°C, short-term up to +125°C |

Note

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

EPIC® ULTRA H-A 3 TBF

| | | |
|----------------------------|--|---------|
| Article number 10423204 | Article description ULTRA H-A 3 TBF | M 20 |
|----------------------------|--|---------|

Last Update (22.09.2017)

©2017 Lapp Group - Technical changes reserved

 Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16