

H07RN-F

Heavy standard construction

H07RN-F, HAR, power and control cable, rubber, heavy, 450/750 V, industrial and agricultural use, class 5/flexible -25°C to +60°C, oil-resistant, flame-retardant

Info

Medium mechanical stress

Oil-resistant



UV-resistant



Oil-resistant



Mechanical resistance



Cold-resistant



Benefits

For mechanically more demanding applications

1000 V AC protected + fixed installation

Arrangements made of single-core, rubber-sheathed cables H07RN-F can be used for short circuit-proof and short-to-ground-proof installations in accordance with IEC 60364-5-52/HD 60364-5-52/VDE 0100 part 520

Last Update (05.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

H07RN-F

Application range

Hand-held and power supply devices according to EN 50565-2

Medium, mechanical stress

Industrial, agricultural use

According to EN 50565-2: Use in dry, damp or wet rooms as well as for fixed installation e.g. on plaster

Product features

Flame-retardant according IEC 60332-1-2

Oil-resistant according to EN 60811-404

Norm references / Approvals

<HAR> H07RN-F design certification according to EN 50525-2-21

Product Make-up

Bare copper stranded wire according to HAR standard

Core insulation: Rubber compound, type EI 4

Outer sheath: Rubber compound type EM 2

Technical Data

Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Core identification code:	Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	4 to 8 x outer diameter (EN 50565-1)
Nominal voltage:	U0/U: 450/750 V
Test voltage:	2500 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Current rating:	According to IEC 60364-5-52/ VDE 0298-4 EN 50565-1/ VDE 0298-565-1
Temperature range:	-25°C to +60°C

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging: Ring ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred packaging (e.g. 1 x 500 m drum or 5 x 100 m rings)

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**LAPP GROUP**

PRODUCT INFORMATION

H07RN-F

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1600096	1 X 1.5	5.7 - 7.1	14.4	59
1600099	1 X 2.5	6.3 - 7.9	24	72
1600097	1 X 4	7.2 - 9	38.4	99
1600098	1 X 6	7.9 - 9.8	57.6	130
1600194	1 X 10	9.5 - 11.9	96	230
1600195	1 X 16	10.8 - 13.4	153.6	320
1600196	1 X 25	12.7 - 15.8	240	450
1600193	1 X 35	14.3 - 17.9	336	605
1600197	1 X 50	16.5 - 20.6	480	825
1600189	1 X 70	18.6 - 23.3	672	1090
1600190	1 X 95	20.8 - 26	912	1405
1600198	1 X 120	22.8 - 28.6	1152	1745
1600191	1 X 150	25.2 - 31.4	1440	1887
1600175	1 X 185	27.6 - 34.4	1776	2274
1600177	1 X 240	30.6 - 38.3	2304	2955
30015435	1 X 300	33.5 - 41.9	2880	3479
1600117	3 G 1	8.3 - 10.7	28.8	130
1600199	2 X 1.5	8.5 - 11	28.8	135
1600103	3 G 1.5	9.2 - 11.9	43.2	165
16001233	4 G 1.5	10.2 - 13.1	57.6	200
16001043	5 G 1.5	11.2 - 14.4	72	240
1600151	7 G 1.5	14.7 - 18.7	100.8	385
1600148	12 G 1.5	17.6 - 22.4	172.8	516
1600259	19 G 1.5	20.7 - 26.3	273.6	800
1600166	24 G 1.5	24.3 - 30.7	345.6	882
1600263	25 G 1.5	25.1 - 25.9	360	920
1600187	2 X 2.5	10.2 - 13.1	48	195
1600118	3 G 2.5	10.9 - 14	72	235
16001053	4 G 2.5	12.1 - 15.5	96	290
16001293	5 G 2.5	13.3 - 17	120	294
1600152	7 G 2.5	17.1 - 21.8	168	520
1600154	12 G 2.5	20.6 - 26.2	288	810
1600156	19 G 2.5	25.5 - 31	456	1200
1600157	24 G 2.5	28.8 - 36.4	576	1650

Last Update (05.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

+44 (0)1908 307200**www.electroustic.co.uk****Electroustic Ltd**

**H07RN-F**

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
1600186	2 X 4	11.8 - 15.1	76.8	270
1600119	3 G 4	12.7 - 16.2	115.2	320
16001063	4 G 4	14 - 17.9	153.6	395
16001303	5 G 4	15.6 - 19.9	192	485
1600161	7 G 4	20.1 - 25.5	268.8	681
1600120	3 G 6	14.1 - 18	172.8	360
16001073	4 G 6	15.7 - 20	230.4	475
16001313	5 G 6	17.5 - 22.2	288	760
1600121	3 G 10	19.1 - 24.2	288	880
16001083	4 G 10	20.9 - 26.5	384	1060
16001093	5 G 10	22.9 - 29.1	480	1300
1600122	3 G 16	21.8 - 27.6	460.8	1090
16001103	4 G 16	23.8 - 30.1	614.4	1345
16001113	5 G 16	26.4 - 33.3	768	1680
16001123	4 G 25	28.9 - 36.6	960	1995
16001133	5 G 25	32 - 40.4	1200	2470
1600124	3 G 35	29.3 - 37.1	1008	1910
16001143	4 G 35	32.5 - 41.4	1344	2645
16001363	5 G 35	35.7 - 45.1	1680	2810
16001153	4 G 50	37.7 - 47.5	1920	3635
1600126	5 G 50	41.8 - 53	2400	4050
16001163	4 G 70	42.7 - 54	2688	4830
16001283	4 G 95	48.4 - 61	3648	6320
16001323	4 G 120	53 - 66	4608	6830
16000883	4 G 150	58 - 73	5760	8320
1600141	4 G 185	64 - 80	7104	9800
1600183	4 G 240	72 - 91	9216	12800

Last Update (05.07.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16