

Cable connector - SH-8ESC58A8LDLS - 1621517

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable connector, straight long, shielded: yes, SPEEDCON locking, M23, Number of positions: 4+4+4+PE / 3+N+PE, Type of contact: Socket, Crimp connection, Cable diameter: 7.5 mm ... 18 mm

Why buy this product

- Transmission of signals, data, and power in just a single connector
- CAT5 data interface
- Reduced connection time with optional SPEEDCON fast locking system
- Safe use in the field, thanks to high degree of protection
- Consistent EMC protection for reliable connection solutions in the industrial environment



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 936323 |
| GTIN | 4046356936323 |
| Weight per Piece (excluding packing) | 130.700 g |
| Custom tariff number | 85366990 |
| Country of origin | Germany |
| Note | Made to Order (non-returnable) |

Technical data

Temperature range

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 130 °C |
|---------------------------------|-------------------|

Data of the insulating body

| | |
|--|--|
| Note | Order information: Crimp contacts, 4x Ø 0.8 mm, 4x Ø 1 mm, 5x Ø 2 mm, order separately |
| Coding | N |
| Insulator material | Polyamide (PA 6.6) |
| Insertion/withdrawal cycles mechanical | 100 |

Cable connector - SH-8ESC58A8LDLS - 1621517

Technical data

Data of the insulating body

| | |
|---|----------------------|
| Contact connection method | Crimp connection |
| Type of contacts | Socket |
| Number of positions | 13 |
| Contact diameter of power contacts | 2 mm |
| Litz wire cross section of power contacts min. | 0.25 mm ² |
| Litz wire cross section of power contacts max. | 4 mm ² |
| Nominal current per power contact at 25°C | 30 A |
| Nominal voltage, power contact | 630 V AC 850 V DC |
| Rated surge voltage | 6 kV |
| Contact diameter of signal contacts | 1 mm |
| Litz wire cross section of signal contacts min. | 0.06 mm ² |
| Litz wire cross section of signal contacts max. | 1 mm ² |
| Nominal current per signal contact at 25°C | 8 A |
| Nominal voltage, signal contact | 50 V |
| Rated surge voltage | 1.5 kV |
| Contact diameter, data contacts | 0.8 mm |
| Litz wire cross section, data contacts, min. | 0.08 mm ² |
| Litz wire cross section, data contacts, max. | 0.5 mm ² |
| Nominal current per data contact at 25°C | 3.6 A |
| Nominal voltage of data contact | 50 V |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | III |
| Degree of pollution | 3 |

Housing data

| | |
|--|--|
| Note | Notes on operation Full occupation with 5 x 4 mm ² for cable and coupler connectors not possible. |
| Housing material | Metal |
| Type of locking | SPEEDCON locking |
| Degree of protection (when plugged in) | IP67 IP68 |
| Thread type | M23 |

Cable seal data

| | |
|---------------------|--------|
| Min. cable diameter | 7.5 mm |
| Max. cable diameter | 18 mm |


Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |


Cable connector - SH-8ESC58A8LDLS - 1621517

Drawings

Schematic diagram



Dimensional drawing



Socket pin assignment, CAT5

Pin version: dimension A = 0.2 mm, socket version: dimension A = 0 mm

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|--|---------|
| EAC | | B.01742 |
|-----|--|---------|

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>