

# Fuse plug - PV-C-M/F-PRO/F-1500/12-EU - 1622148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1500 V/12 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1500 V system voltage

## Product Description

SUNCLIX fuse connector, for 1500 V system voltage, fuse-link nominal current of 12 A, EU version

## Why buy this product

- One-piece design
- Robust, easy-to-install fuse element for outdoor use
- High-quality fuse-link
- Degree of protection: IP68 (24 h/2 m)
- 
- 1500 V



## Key Commercial Data

Packing unit	8 STK
Minimum order quantity	8 STK
GTIN	 4 055626 130576
GTIN	4055626130576
Weight per Piece (excluding packing)	71.030 g
Custom tariff number	85354000
Country of origin	Germany
Note	Made to Order (non-returnable)

## Technical data

### Ambient conditions

Degree of protection (when plugged in)	IP66 / IP68 (2 m / 24 h)
Ambient temperature (operation)	-40 °C ... 50 °C

# Fuse plug - PV-C-M/F-PRO/F-1500/12-EU - 1622148

## Technical data

### General

Rated voltage	1500 V
Fuse-link nominal current	12 A DC (Nominal current of the fuse-link)
Fuse adapter nominal current	11 A DC

### Material

Flammability rating according to UL 94	V0
--	----

### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



## Classifications

### eCl@ss

eCl@ss 5.1	27260702
eCl@ss 8.0	27440102
eCl@ss 9.0	27440107

### ETIM

ETIM 5.0	EC002635
ETIM 6.0	EC002635

### UNSPSC

UNSPSC 13.2	39121409
-------------	----------