

Base strip - GMSTBO 2,5 HV/ 2-GL-7,25 THR - 2199867

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Header, nominal current: 16 A, rated voltage (III/2): 630 V, number of positions: 2, pitch: 7.25 mm, mounting: SMD/THT/THR

Why buy this product

- Suitable for ME/ME MAX electronics housing
- Orthogonal screw/plug-in connection
- Delivery form: box packaging in bulk or tape-on-reel packing for automated mounting
- 7.25 mm pitch for unlimited 600 V UL approval
- THR solderable
-



Key Commercial Data

Packing unit	50 STK
Minimum order quantity	50 STK
GTIN	 4 046356 495301
GTIN	4046356495301
Weight per Piece (excluding packing)	2.550 g
Custom tariff number	85366930
Country of origin	Poland
Note	Made to Order (non-returnable)

Technical data

Dimensions

Pitch	7.25 mm
Dimension a	7.25 mm
Pin dimensions	1,0 x 1,0 mm
Pin spacing	7.25 mm
Hole diameter	1.5 mm

Base strip - GMSTBO 2,5 HV/ 2-GL-7,25 THR - 2199867

Technical data

General

Range of articles	GMSTBO 2,5 HV
Insulating material group	IIIa
Rated surge voltage (III/3)	6 kV
Rated surge voltage (III/2)	6 kV
Rated surge voltage (II/2)	6 kV
Rated voltage (III/3)	400 V
Rated voltage (III/2)	630 V
Rated voltage (II/2)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	16 A
Maximum load current	16 A
Insulating material	LCP
Flammability rating according to UL 94	V0
Number of positions	2

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402
eCl@ss 9.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637
ETIM 6.0	EC002637

Base strip - GMSTBO 2,5 HV/ 2-GL-7,25 THR - 2199867

Classifications

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / VDE Gutachten mit Fertigungsüberwachung / IECCE CB Scheme / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	D
Nominal current IN	16 A	16 A	10 A
Nominal voltage UN	300 V	150 V	300 V

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	D
Nominal current IN	16 A	16 A	10 A
Nominal voltage UN	300 V	150 V	300 V

VDE Gutachten mit Fertigungsüberwachung		http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx	40037875
Nominal current IN	16 A		
Nominal voltage UN	630 V		

Base strip - GMSTBO 2,5 HV/ 2-GL-7,25 THR - 2199867

Approvals

IECEE CB Scheme		http://www.iecee.org/	DE1-52506/A1
Nominal current I _N	16 A		
Nominal voltage U _N	630 V		

EAC		B.01742
-----	--	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm
------------------	--	---

Accessories

Necessary add-on products

Plug - GMSTBT 2,5 HV/2-ST-7,25 GY7035 - 2199757



Plug component, nominal current: 16 A, rated voltage (III/2): 1000 V, number of positions: 2, pitch: 7.25 mm, connection method: Screw connection, color: light gray, contact surface: Tin