

# Housing cover - EH 22,5-C DS/ABS GY7035 - 2201251

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Component housing connection opening on both sides, color: gray, width: 22.5 mm




## Why buy this product

- Item is part of the EH product range
- Tool-free mounting
- Available in overall widths from 22.5 mm ... 90 mm
- Inflammability class HB acc. to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail or the wall



## Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 749947
GTIN	4046356749947
Weight per Piece (excluding packing)	12.530 g
Custom tariff number	85389099
Country of origin	India

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	HB
----------------------------------------	----

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C (depending on power dissipation)
---------------------------------	---------------------------------------------------

### Dimensions

Width	22.5 mm
-------	---------

# Housing cover - EH 22,5-C DS/ABS GY7035 - 2201251

## Technical data

### Standards and Regulations

Flammability rating according to UL 94	HB
----------------------------------------	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### ETIM

ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Accessories

### Necessary add-on products

PCB terminal block - MKDS 3/ 4-5,08 - 1712805



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 4, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green. The article can be aligned to create different nos. of positions!

## Housing cover - EH 22,5-C DS/ABS GY7035 - 2201251

### Accessories

#### PCB terminal block base - MKKDSH 3/ 2 - 1721045



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5 mm, number of positions: 2, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green. The article can be aligned to create different nos. of positions!

---

#### Base strip - MSTBV 2,5/ 4-G - 1753479



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5 mm, color: green, contact surface: Tin, mounting: Wave soldering

---

#### Base strip - MSTBV 2,5/ 4-G-5,08 - 1758034



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

---

#### Base strip - MSTBO 2,5/ 4-GL-5,08 - 1850453



Header, nominal current: 8 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

---

#### Base strip - MSTBO 2,5/ 4-GR-5,08 - 1847123



Header, nominal current: 8 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

## Housing cover - EH 22,5-C DS/ABS GY7035 - 2201251

### Accessories

Printed-circuit board connector - MCO-EH 1,5/5 G1L-3,5 GY7035 - 2202330



Header, nominal current: 8 A, rated voltage (III/2): 160 V, pitch: 3.5 mm

---

Printed-circuit board connector - MCO-EH 1,5/5 G1R-3,5 GY7035 - 2202331



Header, nominal current: 8 A, rated voltage (III/2): 160 V, pitch: 3.5 mm

---

---