

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Fitted plate, for assembly underneath the cover in short design, color: light gray

## Why buy this product

- ▼ Tool-free mounting
- ✓ Available in 40 mm overall width
- ☑ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting



# **Key Commercial Data**

| Packing unit                         | 10 STK          |
|--------------------------------------|-----------------|
| Minimum order quantity               | 10 STK          |
| GTIN                                 | 4 046356 838658 |
| GTIN                                 | 4046356838658   |
| Weight per Piece (excluding packing) | 3.000 g         |
| Custom tariff number                 | 85389099        |
| Country of origin                    | Germany         |

## Technical data

#### General

| Housing type     | Component housing |
|------------------|-------------------|
| Housing material | Polycarbonate     |
| Color (RAL)      | light gray        |

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 105 °C (depending on power dissipation) |
|---------------------------------|--|
|                                 |  |

10/30/2017 Page 1 / 4



# Technical data

## Standards and Regulations

| Flammability rating according to UL 94 | V0  |
|--|---|
| Environmental Product Compliance       |   |
| China RoHS                             | Environmentally friendly use period: unlimited = EFUP-e |

No hazardous substances above threshold values

# Classifications

# eCl@ss

| eCl@ss 4.0 | 27180401 |
|------------|----------|
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |
| eCl@ss 9.0 | 27182702 |

## **ETIM**

| ETIM 3.0 | EC001031 |
|----------|----------|
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC001031 |
| ETIM 6.0 | EC001031 |

#### **UNSPSC**

| UNSPSC 6.01   | 31261501 |
|---------------|----------|
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |

## Accessories

#### Accessories

# Fiber optics

Component housing - HS LC-H-D3/R1XC1 - 2202313



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

10/30/2017 Page 2 / 4



## Accessories

Component housing - HS LC-H-5X2/ R1XC1 - 2202314



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D3/ R2XC1-5,08 - 2202315



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R2XC1-2,54 - 2202316



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R2XC2-2,54 - 2202317



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R2XC5-2,54 - 2202318




Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

10/30/2017 Page 3 / 4



## Accessories

Component housing - HS LC-H-D2/ R2XC10-2,54 - 2202319





Component housing - HS LC-H-D2/ R4XC2-2,54 - 2202320



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R4XC5-2,54 - 2202321



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R4XC9-2,54 - 2202322



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R4XC10-2,54 - 2202323



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com