

# Housing cover - EH 70-C SS/ABS BK9005 - 2201749

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing connection opening on one side, color: black, width: 70 mm

#### Why buy this product

- ▼ Tool-free mounting
- ☑ Available in overall widths from 22.5 mm ... 90 mm
- ☑ Inflammability class HB acc. to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail or the wall



# **Key Commercial Data**

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 908214
GTIN	4046356908214
Weight per Piece (excluding packing)	27.570 g
Custom tariff number	85472000
Country of origin	India

# Technical data

# Standards and Regulations

otandards and regulations		
Flammability rating according to UL 94	НВ	
Ambient conditions		
Ambient temperature (operation)	-40 °C 80 °C (depending on power dissipation)	
Dimensions		
Width	70 mm	

10/30/2017 Page 1 / 3



# Housing cover - EH 70-C SS/ABS BK9005 - 2201749

# Technical data

## Standards and Regulations

	Flammability rating according to UL 94	НВ
--	--	----

#### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

## eCl@ss

eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

#### **ETIM**

ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

## **UNSPSC**

UNSPSC 13.2	31261501

#### Accessories

Accessories

Filler plug

Filler plugs - EH 17,5-FP/ABS BK9005 - 2201841



Component housing, color: black

Filler plugs - EH 17,5-FP/ABS GY7035 - 2201840



Component housing, color: gray

10/30/2017 Page 2 / 3



# Housing cover - EH 70-C SS/ABS BK9005 - 2201749

## Accessories

Necessary add-on products

Base strip - MSTBV 2,5/13-G - 1753657



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 13, pitch: 5 mm, color: green, contact surface: Tin, mounting: Wave soldering

Base strip - MSTBV 2,5/13-G-5,08 - 1758128



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 13, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com