

Housing cover - EH 35-C DS/ABS GY7035 - 2201750

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Component housing connection opening on both sides, color: gray, width: 35 mm



Why buy this product

- Item is part of the EH product range
- Tool-free mounting
- Available in overall widths from 22.5 mm ... 90 mm
- Flammability class HB acc. to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail or the wall

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 908221
GTIN	4046356908221
Weight per Piece (excluding packing)	15.550 g
Custom tariff number	85472000
Country of origin	India

Technical data

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Dimensions

Width	35 mm
-------	-------

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Housing cover - EH 35-C DS/ABS GY7035 - 2201750

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

UNSPSC

UNSPSC 13.2	31261501
-------------	----------

Accessories

Accessories

Filler plug

Filler plugs - EH 17,5-FP/ABS BK9005 - 2201841



Component housing, color: black

Filler plugs - EH 17,5-FP/ABS GY7035 - 2201840



Component housing, color: gray

Necessary add-on products

Housing cover - EH 35-C DS/ABS GY7035 - 2201750

Accessories

PCB terminal block - MKDS 3/ 6-5,08 - 1701144



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 6, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green. The article can be aligned to create different nos. of positions!

PCB terminal block base - MKKDSH 3/ 2 - 1721045



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5 mm, number of positions: 2, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green. The article can be aligned to create different nos. of positions!

Base strip - MSTBV 2,5/ 6-G - 1753518



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 6, pitch: 5 mm, color: green, contact surface: Tin, mounting: Wave soldering

Base strip - MSTBV 2,5/ 6-G-5,08 - 1758050



Header, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 6, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

Base strip - MSTBO 2,5/ 6-GL-5,08 - 1850479



Header, nominal current: 8 A, rated voltage (III/2): 320 V, number of positions: 6, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

Housing cover - EH 35-C DS/ABS GY7035 - 2201750

Accessories

Base strip - MSTBO 2,5/ 6-GR-5,08 - 1847149



Header, nominal current: 8 A, rated voltage (III/2): 320 V, number of positions: 6, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>