

# Electronic housing - ME 17,5 TBUS ADAPTER KMGY - 2201757

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

DIN rail bus adapter for ME and ME-MAX, design width: 17.5 mm, 5 parallel positions, color: light gray (similar to RAL 7035)



## Key Commercial Data

Packing unit	50 STK
GTIN	
GTIN	4046356909037
Weight per Piece (excluding packing)	3.640 g
Custom tariff number	85366990
Country of origin	Germany

## Technical data

### Technical data

Number of positions	5
Current	8 A
Voltage	125 V DC
Housing material	Polyamide
Flammability rating according to UL 94	V0
Color	light gray

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Electronic housing - ME 17,5 TBUS ADAPTER KMGY - 2201757

## Classifications

### eCl@ss

eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27260704
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### ETIM

ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

### UNSPSC

UNSPSC 13.2	31261501
-------------	----------

## Approvals


### Approvals


#### Approvals

EAC / UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

### Approval details


EAC		B.01742
-----	---	---------


UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E118976-20151204
---------------	---	--

Nominal current IN	8 A
Nominal voltage UN	150 V

## Electronic housing - ME 17,5 TBUS ADAPTER KMGY - 2201757

### Approvals

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> E118976-20151204
Nominal current I <sub>N</sub>		6 A
Nominal voltage U <sub>N</sub>		150 V

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>
------------------	---	---