

Electronic housing - HSC-LR 9U KIT 2003 - 2201794

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 99 mm

Why buy this product

- Item is from the ME-IO product range
- Tool-free mounting
- Push-in front connection technology
- Available for up to 54-pos. front connection technology



Key Commercial Data

| | |
|--------------------------------------|---|
| Packing unit | 10 STK |
| Minimum order quantity | 10 STK |
| GTIN |  4 046356 933599 |
| GTIN | 4046356933599 |
| Weight per Piece (excluding packing) | 6.110 g |
| Custom tariff number | 85472000 |
| Country of origin | Germany |

Technical data

General

| | |
|------------------|-------------------|
| Housing type | Component housing |
| Housing material | Polyamide |
| Color (RAL) | orange |

Dimensions

| | |
|--------|---------|
| Length | 99 mm |
| Width | 16.2 mm |

Standards and Regulations

Electronic housing - HSC-LR 9U KIT 2003 - 2201794

Technical data

Standards and Regulations

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 8.0 | 27440309 |
| eCl@ss 9.0 | 27440309 |

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC002638 |
| ETIM 6.0 | EC002638 |

UNSPSC

| | |
|-------------|----------|
| UNSPSC 13.2 | 39121409 |
|-------------|----------|

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

| | | | |
|---------------|--|---|---------------|
| UL Recognized | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 240868 |
|---------------|--|---|---------------|

Accessories

Accessories

Component housing upper part

Electronic housing - HSC-LR 9U KIT 2003 - 2201794

Accessories

Electronic housing - ME-IO 18,8 C 5U 7035 - 2201803



Component housing, Cover, color: light gray, width: 18.9 mm, length: 54.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 7U 7035 - 2201805



Component housing, Cover, color: light gray, width: 18.9 mm, length: 76.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 3U S1 7035 - 2201801



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 4U 7035 - 2201802



Component housing, Cover, color: light gray, width: 18.9 mm, length: 43.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 6U 7035 - 2201804



Component housing, Cover, color: light gray, width: 18.9 mm, length: 65.8 mm, height: 12.2 mm

Electronic housing - HSC-LR 9U KIT 2003 - 2201794

Accessories

Electronic housing - ME-IO 18,8 C 2U 7035 - 2201799



Component housing, Cover, color: light gray, width: 18.9 mm, length: 21.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 3U 7035 - 2201800



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 9U 7035 - 2201806



Component housing, Cover, color: light gray, width: 18.9 mm, length: 98.8 mm, height: 12.2 mm

DIN rail connector

DIN rail bus connectors - ME 18,8 TBUS 1,5/5-ST-3,81KMGY - 2201813



Plug component, nominal current: 8 A, nominal current (Ex): 8 A, nominal voltage (Ex): 125 V, number of positions: 5, pitch: 3.81 mm, color: light gray, contact surface: Gold, Articles with gold-plated contacts, bus connectors for connecting with electronic housings

Necessary add-on products

Printed-circuit board connector - HSCH 2,5-3U/12 9005 - 2201788



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 12, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Electronic housing - HSC-LR 9U KIT 2003 - 2201794

Accessories

Printed-circuit board connector - HSCH 2,5-2U/ 8 9005 - 2201789



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 8, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U-TTTT 9005 - 2201790



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 4, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U-2220 9005 - 2201792



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 6, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item
