

Electronic housing - HSC-LR 5U KIT 2003 - 2201796

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 55 mm

Why buy this product

- Item is from the ME-IO product range
- Tool-free mounting
- Push-in front connection technology
- Available for up to 30-pos. front connection technology

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 933605
GTIN	4046356933605
Weight per Piece (excluding packing)	4.520 g
Custom tariff number	85472000
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	orange

Dimensions

Length	55 mm
Width	16.2 mm

Electronic housing - HSC-LR 5U KIT 2003 - 2201796

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27440309
eCl@ss 9.0	27440309

ETIM

ETIM 4.0	EC001031
ETIM 5.0	EC002638
ETIM 6.0	EC002638

UNSPSC

UNSPSC 13.2	39121409
-------------	----------

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	--	---	---------------

Accessories

Accessories

Component housing upper part

Electronic housing - HSC-LR 5U KIT 2003 - 2201796

Accessories

Electronic housing - ME-IO 18,8 C 5U 7035 - 2201803



Component housing, Cover, color: light gray, width: 18.9 mm, length: 54.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 7U 7035 - 2201805



Component housing, Cover, color: light gray, width: 18.9 mm, length: 76.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 3U S1 7035 - 2201801



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 4U 7035 - 2201802



Component housing, Cover, color: light gray, width: 18.9 mm, length: 43.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 6U 7035 - 2201804



Component housing, Cover, color: light gray, width: 18.9 mm, length: 65.8 mm, height: 12.2 mm

Electronic housing - HSC-LR 5U KIT 2003 - 2201796

Accessories

Electronic housing - ME-IO 18,8 C 2U 7035 - 2201799



Component housing, Cover, color: light gray, width: 18.9 mm, length: 21.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 3U 7035 - 2201800



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 9U 7035 - 2201806



Component housing, Cover, color: light gray, width: 18.9 mm, length: 98.8 mm, height: 12.2 mm

DIN rail connector

DIN rail bus connectors - ME 18,8 TBUS 1,5/5-ST-3,81KMGY - 2201813



Plug component, nominal current: 8 A, nominal current (Ex): 8 A, nominal voltage (Ex): 125 V, number of positions: 5, pitch: 3.81 mm, color: light gray, contact surface: Gold, Articles with gold-plated contacts, bus connectors for connecting with electronic housings

Necessary add-on products

Printed-circuit board connector - HSCH 2,5-3U/12 9005 - 2201788



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 12, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Electronic housing - HSC-LR 5U KIT 2003 - 2201796

Accessories

Printed-circuit board connector - HSCH 2,5-2U/ 8 9005 - 2201789



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 8, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U-TTTT 9005 - 2201790



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 4, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U-2220 9005 - 2201792



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 6, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item
