

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing, Cover, color: light gray, width: 18.9 mm, length: 21.8 mm, height: 12.2 mm

## Why buy this product

- ▼ Tool-free mounting
- ✓ Available in overall widths from 18.8 mm
- ☑ Inflammability class V0 according to UL 94
- Front push-in connection technology
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting



## **Key Commercial Data**

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 911603
GTIN	4046356911603
Weight per Piece (excluding packing)	3.700 g
Custom tariff number	85389099
Country of origin	Germany

## Technical data

#### General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	light gray

#### Ambient conditions

Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)

11/02/2017 Page 1 / 4



## Technical data

## Dimensions

Length	21.8 mm
Constructional height	12.2 mm
Width	18.9 mm

## Technical data

Number of positions	5

## Standards and Regulations


Flammability rating according to UL 94	V0

## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values


## **Drawings**

## Dimensional drawing





## Dimensional drawing



## Classifications

## eCl@ss

eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

## **ETIM**

ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

## **UNSPSC**

UNSPSC 13.2	31261501

## Approvals

## Approvals

11/02/2017 Page 2 / 4



## Approvals

Approvals

**UL** Recognized

Ex Approvals

#### Approval details

**UL** Recognized



http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm FILI

FILE E 240868

## Accessories

#### Accessories

Fiber optics

Component housing - HS LC-H-D2/ R4XC2-2,54 - 2202320



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R4XC5-2,54 - 2202321



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Component housing - HS LC-H-D2/ R4XC9-2,54 - 2202322



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

11/02/2017 Page 3 / 4



## Accessories

Component housing - HS LC-H-D2/ R4XC10-2,54 - 2202323



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), color: transparent

Phoenix Contact 2017 @ - all rights reserved http://www.phoenixcontact.com