

## Electronic housing - ME 17,5 UT/FE BUS/ 5+2 KMGY - 2201855

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




, length: 99 mm, Component housing with vents, Lower part, Cross connection: integrated bus connector, color: light gray, width: 17.5 mm, height: 114.5 mm, number of positions cross connector: 5+2

### Why buy this product

- ✓ Item is from the ME product range
- ✓ Tool-free mounting
- ✓ Available in overall widths from 12.5 mm to 90 mm, modular extension is possible
- ✓ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- ✓ Can be mounted on the DIN rail
- ✓ Optional bus connector that is either integrated or mounted on the DIN rail

RoHS

### Key Commercial Data

Packing unit	10 STK
GTIN	 4 046356 990646
GTIN	4046356990646
Weight per Piece (excluding packing)	37.820 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

### Technical data

#### General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	light gray

#### Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
---	------------------

## Electronic housing - ME 17,5 UT/FE BUS/ 5+2 KMGY - 2201855

### Technical data

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

#### Dimensions

Length	99 mm
Constructional height	114.5 mm
Width	17.5 mm
Depth	99 mm

#### Technical data

Number of positions	12
---------------------	----

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

### Classifications

#### eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

#### ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

#### UNSPSC

UNSPSC 13.2	31261501
-------------	----------

### Approvals

#### Approvals

#### Approvals

#### EAC

#### Ex Approvals

## Electronic housing - ME 17,5 UT/FE BUS/ 5+2 KMGY - 2201855

### Approvals

#### Approval details

EAC	<b>EAC</b>	B.01742
-----	------------	---------

### Accessories

#### Accessories

##### Filler plug

Electronic housing - ME B-KA KMGY - 2706302



Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS terminal opening, (male side)

Electronic housing - ME B-SA/NS 35 KMGY - 2706700



Terminal cover, 1 strip covers up to 12 terminal points, for ME-BUS male side, (female side)

### Mounting material

Electronic housing - ME LPZS - 2906911



Component housing

Components of electronic housing - ME DH 27 NS 35 KMGY - 2706289



Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 27 mm

## Electronic housing - ME 17,5 UT/FE BUS/ 5+2 KMGY - 2201855

### Accessories

Components of electronic housing - ME DH 36 NS 35 KMGY - 2706292

Spacers, for protection of the input or output contacts for DIN rail NS 35, width [B] 36 mm



---

Electronic housing - E/ME TBUS NS35 GY - 2713780



End clamp, stable construction for DIN rail bus connector

---

Printed-circuit board connector - MCVR 1,5/ 5-ST-3,81 GY7035 AU - 1719684



Plug component, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 5, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: light gray, contact surface: Gold

---

Printed-circuit board connector - MC 1,5/ 5-ST-3,81 GY7035 AU - 1719697

Plug component, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 5, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: light gray, contact surface: Gold

---

Printed-circuit board connector - IMC 1,5/ 5-ST-3,81 GY7035 AU - 1719707

Plug component, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 5, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: light gray, contact surface: Gold

---

### Necessary add-on products

Electronic housing - ME 17,5 OT-FKDSO KMGY - 2200322



, length: 99 mm, Component housing, Upper part, color: light gray, width: 17.5 mm, height: 38.5 mm

## Electronic housing - ME 17,5 UT/FE BUS/ 5+2 KMGY - 2201855

### Accessories

Electronic housing - ME 17,5 OT-MSTBO KMGY - 2853747



, length: 99 mm, Component housing, Upper part, color: light gray, width: 17.5 mm, height: 38.5 mm

---

Electronic housing - ME 17,5 OTU-MKDSO KMGY - 2278940



, length: 99 mm, Component housing, Upper part, color: light gray, width: 17.5 mm, height: 38.5 mm

---

Electronic housing - ME 17,5 OTP-MSTBO PS KMGY - 2279253



, length: 99 mm, Component housing, Upper part, color: light gray, width: 17.5 mm, height: 38.5 mm

---