

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Component housing, Lower part, Cross connection: DIN rail bus connector, color: light gray, width: 18.9 mm, length: 113.3 mm, height: 57.7 mm, number of positions cross connector: 5

Why buy this product

- ▼ Tool-free mounting
- ✓ Available in overall widths from 18.8 mm
- ☑ Inflammability class V0 according to UL 94
- Front push-in connection technology
- Can be mounted on the DIN rail
- Optional with bus connector for DIN rail mounting
- Functional earth ground contact integrated in the housing part



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 946438
GTIN	4046356946438
Weight per Piece (excluding packing)	38.230 g
Custom tariff number	85389099
Country of origin	Germany

Technical data

General

Housing type	Component housing
Housing material	Polyamide
Color (RAL)	light gray (7035)

Ambient conditions

11/02/2017 Page 1 / 7



Technical data

Ambient conditions

Ambient temperature (storage/transport)	-40 °C 70 °C
Ambient temperature (assembly)	-5 °C 100 °C
Ambient temperature (operation)	-40 °C 105 °C (depending on power dissipation)

Dimensions

Length	113.3 mm
Constructional height	57.7 mm
Width	18.9 mm

Technical data

Power dissipation without gap	2.8 W
, and all all all all all all all all all al	

Standards and Regulations


Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 3.0	EC001031

11/02/2017 Page 2 / 7



Classifications

ETIM

ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approvals

Approvals

UL Recognized

Ex Approvals

Approval details

UL Recognized



http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

FILE E 240868

Accessories

Accessories

Component housing upper part

Electronic housing - ME-IO 18,8 C 5U 7035 - 2201803



Component housing, Cover, color: light gray, width: 18.9 mm, length: 54.8 mm, height: 12.2 mm

11/02/2017 Page 3 / 7



Accessories

Electronic housing - ME-IO 18,8 C 7U 7035 - 2201805



Component housing, Cover, color: light gray, width: 18.9 mm, length: 76.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 3U S1 7035 - 2201801



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 4U 7035 - 2201802



Component housing, Cover, color: light gray, width: 18.9 mm, length: 43.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 6U 7035 - 2201804



Component housing, Cover, color: light gray, width: 18.9 mm, length: 65.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 2U 7035 - 2201799



Component housing, Cover, color: light gray, width: 18.9 mm, length: 21.8 mm, height: 12.2 mm

11/02/2017 Page 4 / 7



Accessories

Electronic housing - ME-IO 18,8 C 3U 7035 - 2201800



Component housing, Cover, color: light gray, width: 18.9 mm, length: 32.8 mm, height: 12.2 mm

Electronic housing - ME-IO 18,8 C 9U 7035 - 2201806



Component housing, Cover, color: light gray, width: 18.9 mm, length: 98.8 mm, height: 12.2 mm

DIN rail connector

DIN rail bus connectors - ME 18,8 TBUS 1,5/5-ST-3,81KMGY - 2201813



Plug component, nominal current: 8 A, nominal current (Ex): 8 A, nominal voltage (Ex): 125 V, number of positions: 5, pitch: 3.81 mm, color: light gray, contact surface: Gold, Articles with gold-plated contacts, bus connectors for connecting with electronic housings

Necessary add-on products

Printed-circuit board connector - HSCH 2,5-3U/12 9005 - 2201788



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 12, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U/ 8 9005 - 2201789



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 8, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

11/02/2017 Page 5 / 7



Accessories

Printed-circuit board connector - HSCH 2,5-2U-TTTT 9005 - 2201790



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 4, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Printed-circuit board connector - HSCH 2,5-2U-2220 9005 - 2201792



Header, nominal current: 8 A, rated voltage (III/2): 300 V, number of positions: 6, pitch: 5 mm, connection method: Plug / solder connection, color: black, contact surface: Tin, mounting: Soldering, Please observe the derating curve of the item

Electronic housing - HSC-LR 5U KIT 2003 - 2201796



Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 55 mm

Electronic housing - HSC-LR 3U KIT 2003 - 2201797



Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 33 mm

Electronic housing - HSC-LR 7U KIT 2003 - 2201795



Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 77 mm

11/02/2017 Page 6 / 7



Accessories

Electronic housing - HSC-LR 9U KIT 2003 - 2201794



Component housing, Lock and Release system, color: orange, width: 16.2 mm, length: 99 mm

Phoenix Contact 2017 @ - all rights reserved http://www.phoenixcontact.com