

Electronic housing - UM-BASIC/PRO AU N 73 CM - 2202035

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Panel mounting base, Cover, color: transparent, width: 73 mm, length: 1000 mm, height: 24 mm, Note: max. length of the cover = PCB length = 19 mm



Why buy this product

- Item is from the UM-BASIC/UM-PRO product range
- PVC press-drawn section (UM-BASIC) or PA (UM-PRO)
- Available in individual lengths
- Available in the overall widths of 72 mm, 108 mm, and 122 mm
- Variety of connection technologies
- Can be mounted on the DIN rail



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626005461
Custom tariff number	39169010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

General

Housing type	Panel mounting base
Housing material	PC
Color (RAL)	transparent

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	1000 mm
--------	---------

Electronic housing - UM-BASIC/PRO AU N 73 CM - 2202035

Technical data

Dimensions

Constructional height	24 mm
Width	73 mm

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 6.0	27182003
eCl@ss 8.0	27182701
eCl@ss 9.0	27182701

ETIM

ETIM 5.0	EC002779
ETIM 6.0	EC002779

UNSPSC

UNSPSC 13.2	31261501
-------------	----------

Accessories

Necessary add-on products

Electronic housing - UM-BASIC/PRO LID-73N KMGY - 2202034

Panel mounting base, color: light gray

