

Electronic housing - HCS-T MICRO 1 C 1 1 7035 - 2203125

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Handheld housing, T-Micro, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, closed

Why buy this product

- ✓ Suitable for handheld devices

- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20 °C to +50 °C
- ✓ Flammability rating UL 94-V0



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 376837
GTIN	4055626376837
Weight per Piece (excluding packing)	64.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	48 mm
-------	-------

10/27/2017 Page 1 / 2



Electronic housing - HCS-T MICRO 1 C 1 1 7035 - 2203125

Technical data

Dimensions

Height	150 mm
Depth	28 mm

Standards and Regulations

Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com