

Electronic housing - HCS-T MICRO X C 1 1 7035 - 2203126

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Handheld housing, T-Micro, light gray, consisting of two half shells, two front plates with screws, front 1.1 mm recessed, closed with keypad slot

Why buy this product

- Item is from the HCS product range
- Suitable for handheld devices
- Ergonomic straight or staggered housing design
- ☑ Integration of LCD displays and membrane keypads
- Degree of protection: up to IP54
- Temperature range: -20 °C to +50 °C
- ☑ Shock-resistant ABS plastic
- Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 376844
GTIN	4055626376844
Weight per Piece (excluding packing)	91.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing	
Housing material	ABS	
Color (RAL)	light gray	
Dimensions		

Width	48 mm

10/27/2017 Page 1 / 2



Electronic housing - HCS-T MICRO X C 1 1 7035 - 2203126

Technical data

Dimensions

Height	150 mm	
Depth	28 mm	
Standards and Regulations		
Flammability rating according to UL 94	VO	

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

10/27/2017 Page 2 / 2