

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Handheld housing, T-Maxi, light gray, consisting of two half shells with screws, front 1.1 mm recessed, with window and keypad slot

Why buy this product

- ✓ Item is from the HCS product range
- ✓ Suitable for handheld devices
- ✓ Ergonomic straight or staggered housing design
- ✓ Integration of LCD displays and membrane keypads
- ✓ Degree of protection: up to IP54
- ✓ Temperature range: -20 °C to +50 °C
- ✓ Shock-resistant ABS plastic
- ✓ Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 376943
GTIN	4055626376943
Weight per Piece (excluding packing)	366.700 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	116 mm
-------	--------

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Technical data

Dimensions

Height	253 mm
Depth	46 mm

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031