PHŒNIX CONTACT

Electronic housing - HCS-C MINI 1W C C C 7035 - 2203147

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Handheld housing, C-Mini, light gray, consisting of two half shells with screws, front 1.1 mm recessed with window and keypad slot

Why buy this product

☑ Item is from the HCS product range

☑ Suitable for handheld devices

☑ Ergonomic straight or staggered housing design

☑ Integration of LCD displays and membrane keypads

☑ Degree of protection: up to IP54

☑ Temperature range: -20 °C to +50 °C

☑ Shock-resistant ABS plastic

☑ Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 377018
GTIN	4055626377018
Weight per Piece (excluding packing)	88.100 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	70.5 mm

Electronic housing - HCS-C MINI 1W C C C 7035 - 2203147

Technical data

Dimensions

Height	110 mm
Depth	26 mm

Standards and Regulations

Flammability rating according to UL 94	V0

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Electroustic Ltd   www.electroustic.co.uk   +44 (0)1908 307200