

## Electronic housing - HCS-C MEDIUM C C 1 1 7035 - 2203161

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Handheld housing, C-Medium, light gray, front level closed, consisting of two half shells, two front plates with screws

### Why buy this product

- ✓ Item is from the HCS product range
- ✓ Suitable for handheld devices
- ✓ Ergonomic straight or staggered housing design
- ✓ Integration of LCD displays and membrane keypads
- ✓ Degree of protection: up to IP54
- ✓ Temperature range: -20 °C to +50 °C
- ✓ Shock-resistant ABS plastic
- ✓ Flammability rating UL 94-V0

RoHS

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 377742
GTIN	4055626377742
Weight per Piece (excluding packing)	203.500 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

#### Dimensions

Width	87 mm
-------	-------

## Electronic housing - HCS-C MEDIUM C C 1 1 7035 - 2203161

### Technical data

#### Dimensions

Height	164 mm
Depth	31 mm

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Classifications

#### eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

#### ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031