

# Electronic housing - HCS-C MAXI 1W 2X9V 1 1 7035 - 2203170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Handheld housing, C-Maxi, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 2x 9 V battery

### Why buy this product

- ✓ Suitable for handheld devices
- ☑ Integration of LCD displays and membrane keypads
- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20 °C to +50 °C
- ✓ Flammability rating UL 94-V0



# **Key Commercial Data**

Packing unit	1 STK
GTIN	4 055626 377261
GTIN	4055626377261
Weight per Piece (excluding packing)	232.200 g
Custom tariff number	39269097
Country of origin	Germany

## Technical data

#### General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

### **Dimensions**

Width	94 mm

10/27/2017 Page 1 / 2



# Electronic housing - HCS-C MAXI 1W 2X9V 1 1 7035 - 2203170

# Technical data

# Dimensions

Height	182.5 mm
Depth	39 mm

# Standards and Regulations

Flammability rating according to UL 94	V0

# Classifications

# eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### **ETIM**

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com