

## Electronic housing - DCS 5,7 M C O BP C 7035 - 2203173

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Display housing, 5.6"/5.7", light gray, central window, front level, for battery pack consisting of two half shells, with screws and battery pack contacts

### Why buy this product

- Item belongs to the DCS product range
- Display housings for mobile and stationary operator panels
- Integration of TFT display and membrane keypads
- Degree of protection: up to IP54
- Temperature range: -20°C to +50°C
- Shock-resistant ABS plastic
- Flammability rating UL 94-V0



### Key Commercial Data

Packing unit	2 STK
GTIN	 4 055626 377292
GTIN	4055626377292
Weight per Piece (excluding packing)	300.000 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

#### General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

#### Dimensions

Width	224 mm
Height	157 mm

## Electronic housing - DCS 5,7 M C O BP C 7035 - 2203173

### Technical data

#### Dimensions

Depth	40 mm
-------	-------

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Classifications

#### eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

#### ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031