

Electronic housing - DCS 5,7 M 1F RL W C 7035 - 2203174

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Display housing, 5.6"/5.7", light gray, consisting of two half shells with screws, window in the middle. Front 1.1 mm recessed, keypad areas on the left and right recessed for wall installation

Why buy this product

- ☑ Display housings for mobile and stationary operator panels
- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20°C to +50°C
- ▼ Flammability rating UL 94-V0



Key Commercial Data

Packing unit	2 STK
GTIN	4 055626 378305
GTIN	4055626378305
Weight per Piece (excluding packing)	300.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	224 mm
Height	157 mm

10/27/2017 Page 1 / 2



Electronic housing - DCS 5,7 M 1F RL W C 7035 - 2203174

Technical data

Dimensions

Depth	40 mm	
Standards and Regulations		
Flammability rating according to UL 94	V0	

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com