

# Electronic housing - DCS 5,7 L 1F R W C 7035 - 2203176

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Display housing, 5.6"/5.7", light gray, consisting of two half shells with screws, window on the left. Front 1.1 mm recessed, keypad area on the right recessed for wall installation

### Why buy this product

- ☑ Display housings for mobile and stationary operator panels
- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20°C to +50°C
- ▼ Flammability rating UL 94-V0



# **Key Commercial Data**

Packing unit	2 STK
GTIN	4 055626 378329
GTIN	4055626378329
Weight per Piece (excluding packing)	300.000 g
Custom tariff number	39269097
Country of origin	Germany

### Technical data

### General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

#### **Dimensions**

Width	224 mm
Height	157 mm

10/27/2017 Page 1 / 2



# Electronic housing - DCS 5,7 L 1F R W C 7035 - 2203176

# Technical data

# Dimensions

Depth	40 mm
Standards and Regulations	
Flammability rating according to UL 94	V0

# Classifications

### eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

### **ETIM**

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com