

Electronic housing - DCS 7 M C O C 1 7035 - 2203183

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Display housing, 7", light gray, central window, front level, consisting of two half shells, four front plates with screws

Why buy this product

- ☑ Item belongs to the DCS product range
- ☑ Display housings for mobile and stationary operator panels
- Integration of TFT display and membrane keypads
- ☑ Degree of protection: up to IP54
- ✓ Temperature range: -20°C to +50°C
- Shock-resistant ABS plastic
- Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	2 STK
GTIN	4 055626 378374
GTIN	4055626378374
Weight per Piece (excluding packing)	290.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	224 mm
Height	157 mm

10/27/2017 Page 1 / 2



Electronic housing - DCS 7 M C O C 1 7035 - 2203183

Technical data

Dimensions

Depth	40 mm	
Standards and Regulations		
Flammability rating according to UL 94	V0	

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

10/27/2017 Page 2 / 2