

Electronic housing - DCS 15 M C O S C 7035 - 2203191

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Display housing, 15", light gray, central window, front level, with cutout for connection technology angle plate consisting of two half shells with screws

Why buy this product

- ✓ Item belongs to the DCS product range
- ✓ Display housings for mobile and stationary operator panels
- ✓ Integration of TFT display and membrane keypads
- ✓ Degree of protection: up to IP54
- ✓ Temperature range: -20°C to +50°C
- ✓ Shock-resistant ABS plastic
- ✓ Flammability rating UL 94-V0

RoHS

Key Commercial Data

Packing unit	4 STK
GTIN	 4 055626 378459
GTIN	4055626378459
Weight per Piece (excluding packing)	756.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

General

Housing type	Complete housing
Housing material	ABS
Color (RAL)	light gray

Dimensions

Width	362 mm
Height	286 mm

Electronic housing - DCS 15 M C O S C 7035 - 2203191

Technical data

Dimensions

Depth	62 mm
-------	-------

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27180506
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
ETIM 6.0	EC001031