


## (f) HIRSCHMANN

Product information MAB 6 930 011-200

| Name                         | MAB 6  |
|------------------------------|--|
| Manie                        |  |
|                              |  |
|                              | panel-mounted socket with flange; solder joint |
| Delivery informations        | parter internet obseter manage, oneon joint    |
| Availability                 | available                                      |
| Product description          |  |
| Туре                         | MAB 6  |
| Order No.                    | 930 011-200                                    |
| Type of contact              | female   |
| Description                  | panel-mounted socket with flange; solder joint |
| Number of contacts           | 6  |
| Conductor size               | <= 0.34 mm <sup>2</sup>                        |
| Technical data               |  |
| LF output "Phone"            | EN 60 130-09                                   |
| Pole arrangement DIN         | DIN 45 322                                     |
| Rated current                | 4A   |
| Rated voltage                | AC/DC 34 V                                     |
| Type of termination          | solder   |
| Material                     |  |
| Contact material (socket)    | brass  |
| Contact surface material     | tin plated                                     |
| Contact bearer material      | PA 66/UL standard 94V-2                        |
| Housing material             | steel, nickel-plated                           |
| Environmental conditions     |  |
| Protection class (IEC 60529) | IP 30  |
| Temperature range            | -20 °C to +60 °C                               |
| Picture                      |  |
| Drawing                      | 28.5   |



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.