



Product information MAK 50 S UM schwarz/black 931 092-100

Name	MAK 50 S UM schwarz/black
	socket with insulated handle; solder joint
Delivery informations	
Availability	available
Product description	
Туре	MAK 50 S UM schwarz/black
Order No.	931 092-100
Type of contact	female
Description	socket with insulated handle; solder joint
Housing Color	black
Number of contacts	5
Conductor size	$\leq 0.34 \text{ mm}^2$
Technical data	
LF output "Phone"	EN 60 130-09
Pole arrangement DIN	DIN 41 524
Rated current	4A
Rated voltage	AC/DC 34 V
Cable diameter	5.5 mm
Type of termination	solder
Material	
Contact material (socket)	brass
Contact surface material	tin plated
Contact bearer material	PA 66/UL standard 94V-2
Housing material	PE
Environmental conditions	
Protection class (IEC 60529)	IP 30
Temperature range	-20 °C to +60 °C
Scope of delivery and accessories	
Packaging	industry package, box; individual parts not assembled, sorted

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture Drawing

for cable dia. 5.5 mm

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.