



Product information G 4 KW 1 F 2m 931 805-602


Name	G 4 KW 1 F 2m
	Cable socket, with integrally molded lead
Delivery informations	
Availability	available
Product description	
Description	Cable socket, with integrally molded lead
Туре	G 4 KW 1 F 2m
Order No.	931 805-602
Type of contact	forked spring
Number of contacts	4
Cable material	PVC
Cable length	2 m
Conductor size	4 x 0.75 mm ²
Cable type	A03 W-F 4X0,75
Standard	DIN VDE 0627 / IEC 61984
Housing Color	grey
Technical data	
Rated voltage	AC/DC 50 V
Rated current	10 A
Contact resistance	<= 4 m0hm
Material	
Contact surface material	Sn
Contact bearer material	PA PA
Housing material	PA PA
Environmental conditions	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 HB
Contact bearer	94 HB
Approvals	
VDE	VDE
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Scope of delivery	1 cable socket with integrally molded lead, 1 central screw M 3 x 20, 1 gasket
Accessories to order separately	can be plugged into G 4 E 1 M grau/grey, G 4 A 5 M grau/grey, G 4 A 1 M

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture

Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.