

## **h** <u>HIRSCHMANN</u>

Product information GDM 2011 grau/grey 931 957-106

1			
NR	m	ю	

GDM 2011 grau/grey




	cable socket with central screw M 3 x 35		
Delivery informations			
Availability	available		
Product description			
Description	cable socket with central screw M 3 x 35		
Туре	GDM 2011 grau/grey		
Order No.	931 957-106		
Other standard types	black housing, Order no. 931 957-100		
Number of contacts	2 + PE		
Cable gland	PG 11		
Conductor size	max. 1.5 mm <sup>2</sup>		
Standard	DIN EN 175 301-803-A		
Housing Color	û.an		
Construction type	A		
Technical data			
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm		
Rated voltage	AC/DC 250 V		
Rated current	16 A		
Contact resistance	<= 4 m0hm		
Type of termination	screw		
Suitable cables	6 mm to 9 mm diameter		
Mounting	central nut		
Material			
Contact surface material	Sn		
Contact bearer material	PA		
Housing material	PA		
Environmental conditions			
Protection class (IEC 60529)	IP 65 (gasket necessary)		
Pollution severity	3		
Temperature range	-40 °C to +125 °C		
Inflammability class			
Housing	94 HB		
Contact bearer	94 HB		
Approvals			
VDE	VDE		
SEV	SEV		
CSA	CSA		
Packing unit			
Packaging unit	200 pieces		
Scope of delivery and accessories			
Accessories to order separately	(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-002;		
	knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001		

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.