




Product information
CM 06 EA 14S-6 S
932 458-100

Name		CM 06 EA 14S-6 S
		
		Straight cable socket, strain relief by means of a clamp
Delivery informations		
Availability	available	
Product description		
Description	Straight cable socket, strain relief by means of a clamp	
Type	CM 06 EA 14S-6 S	
Order No.	932 458-100	
Number of contacts	6	
Cable gland	PG 11	
Cable diameter	8 mm to 10 mm	
Conductor size	max. 1 mm ²	
Standard	MIL-C 5015 bzw. VG 95 342	
Housing Color	black	
Technical data		
Pin dimensions	1.6 mm	
Rated voltage	AC/DC 50 V	
Rated current	10 A	
Contact resistance	<= 5 mOhm	
Type of termination	solder	
Shell size	14S	
Material		
Contact surface material	Ag	
Contact bearer material	PA 66-GF 25	
Housing material	PA 66-GF 25	
O-Ring	NBR	
Environmental conditions		
Protection class (IEC 60529)	IP 67	
Pollution severity	3	
Temperature range	-40 °C to +90 °C	
Inflammability class		
Flammability, UL standard	94 V-1	
Packing unit		
Packaging unit	100 pieces	
Scope of delivery and accessories		
Scope of delivery	1 cable socket, not assembled, assembly instructions	
Accessories to order separately	can be plugged into CM 02 E 14S-6 P; cap CM 06 SD 14S, order no. 831 621-100	



Picture
Drawing

