



**Product information**  
**GSA 3000 A schwarz/black**  
**932 598-500**

Name		GSA 3000 A schwarz/black
		
		appliance connector with retaining nut, without screws, longitudinal slots, closed nut
Delivery informations		
Availability		available
Product description		
Description		appliance connector with retaining nut, without screws, longitudinal slots, closed nut
Type		GSA 3000 A schwarz/black
Order No.		932 598-500
Number of contacts		3 + PE
Standard		DIN EN 175 301-803-A
Housing Color		black
Construction type		A
Technical data		
Rated voltage		AC/DC 400 V
Rated current		16 A
Contact resistance		<= 4 mOhm
Type of termination		solder, holes for possibility of soldering on both sides (ground contacts: screw)
Mounting		screw
Material		
Contact surface material		Sn
Contact bearer material		PA
Housing material		PA
Environmental conditions		
Protection class (IEC 60529)		IP 65 (gasket necessary) (mated)
Pollution severity		3
Temperature range		-40 °C to +125 °C
Inflammability class		
Contact bearer		94 V-0
Approvals		
UR		UR
VDE		VDE
SEV		SEV
CSA		CSA
Packing unit		
Packaging unit		200 pieces
Scope of delivery and accessories		
Accessories to order separately		(NBR) flat gasket GSA 200-4, Order no. 730 843-002; (EPDM) flat gasket GSA 200-7, Order no. 730 268-003



Picture  
Drawing

