



## Product information GDML 3011 LED 24 RG schwarz/black 932 857-002


Name	GDML 3011 LED 24 RG schwarz/black
	function indicator (glow lamp) (2 LED's) for pressure switch
Delivery informations	
Availability	available
Product description	
Description	function indicator (glow lamp) (2 LED's) for pressure switch
Туре	GDML 3011 LED 24 RG schwarz/black
Order No.	932 857-002
Number of contacts	3 + PE
Cable gland	PG 11 (black)
Conductor size	max. 1 mm²
Standard	DIN EN 175 301-803-A
Housing Color	transparent
Construction type	A
Description of Wiring	,
LED color	LED green (3)LED red (2)
Other characteristics	for pressure switch
Technical data	is present since.
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm
Rated voltage	DC 24 V
Rated current	8A
Contact resistance	<= 4 m0hm
Type of termination	screw
Suitable cables	4.5 mm to 11 mm diameter
Mounting	central nut
Material	Container
Contact surface material	Sn Sn
Contact bearer material	PA PA
Housing material	PA PA
Environmental conditions	,,,,
Protection class (IEC 60529)	IP 65 (gasket necessary)
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 HB
Contact bearer	94 HB
Packing unit	
Packaging unit	50 pieces
Scope of delivery and accessories	
Accessories to order separately	(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-0
	knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture

Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.