




Product information
GMNL 209 NJ LED 24 HH grau/grey
933 388-106

Name		GMNL 209 NJ LED 24 HH grau/grey
		
		function indicator (LED) with protective circuit (diode)
Delivery informations		
Availability		available
Product description		
Description		function indicator (LED) with protective circuit (diode)
Type		GMNL 209 NJ LED 24 HH grau/grey
Order No.		933 388-106
Other standard types		transparent housing, locking screw black: Order No. 933 388-100
Number of contacts		2 + PE
Cable gland		PG 9 (grey)
Cable diameter		6.5 mm
Conductor size		max. 1.5 mm ²
Standard		DIN EN 175 301-803-B
Housing Color		transparent
Construction type		B
Description of Wiring		
LED color		LED red
Suppressor		diode
Technical data		
Pin dimensions		6.3 mm x 0.8 mm
Rated voltage		DC 24 V
Rated current		8 A
Contact resistance		<= 4 mOhm
Type of termination		screw / cable shoe / cable eye
Suitable cables		4.5 mm to 7 mm diameter
Mounting		central screw
Material		
Contact surface material		Sn
Contact bearer material		PA
Housing material		PA
Environmental conditions		
Protection class (IEC 60529)		IP 65
Pollution severity		3
Temperature range		-40 °C to +90 °C
Inflammability class		
Housing		94 V-1
Contact bearer		94 HB
Approvals		
UR		UR
Packing unit		
Packaging unit		50 pieces

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Scope of delivery and accessories

Picture

Drawing

