



**Product information**

**GMNL 209 NJ LED 230 YE schwarz/black**

**933 715-100**

Name	GMNL 209 NJ LED 230 YE schwarz/black
	
	function indicator (LED) with freewheeling diode
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	function indicator (LED) with freewheeling diode
Type	GMNL 209 NJ LED 230 YE schwarz/black
Order No.	933 715-100
Other standard types	transparent housing, cable gland grey; Order No. 933 715-106
Number of contacts	2 + PE
Cable gland	PG 9 (black)
Cable diameter	6.5 mm
Conductor size	max. 1.5 mm <sup>2</sup>
Standard	DIN EN 175 301-803-B
Housing Color	transparent
Construction type	B
<b>Description of Wiring</b>	
LED color	LED yellow
<b>Technical data</b>	
Pin dimensions	6.3 mm x 0.8 mm
Rated voltage	AC/DC 250 V
Rated current	8 A
Contact resistance	<= 4 mOhm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central screw
<b>Material</b>	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
<b>Environmental conditions</b>	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
<b>Inflammability class</b>	
Housing	94 V-1
Contact bearer	94 HB
<b>Approvals</b>	
UR	UR
<b>Packaging unit</b>	
Packaging unit	50 pieces
<b>Scope of delivery and accessories</b>	
Accessories to order separately	(NBR) flat gasket GMN 209-3, Order No. 733 273-002; knurled screw GDM 3011-8, Order No. 732 574-001; stainless steel screw GDM 3011 RF-1, Order No. 734 363-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture  
Drawing

