




**Product information**  
**GML 216 NJ LED 24 HH grau/grey**  
**934 458-003**

|   |   |
|---|---|
| <b>Name</b>   |   |
| GML 216 NJ LED 24 HH grau/grey  |   |
|  |   |
| function indicator (LED) with protective circuit (diode)                          |   |
| <b>Delivery informations</b>  |   |
| <b>Availability</b>   | available   |
| <b>Product description</b>  |   |
| <b>Description</b>  | function indicator (LED) with protective circuit (diode)        |
| <b>Type</b>   | GML 216 NJ LED 24 HH grau/grey                                  |
| <b>Order No.</b>  | 934 458-003   |
| <b>Other standard types</b>   | transparent housing, locking screw black: Order No. 934 460-002 |
| <b>Number of contacts</b>   | 2 + PE  |
| <b>Cable gland</b>  | M 16 (grey)   |
| <b>Conductor size</b>   | max. 1.5 mm <sup>2</sup>  |
| <b>Standard</b>   | industrial standard (11 mm)                                     |
| <b>Housing Color</b>  | transparent   |
| <b>Construction type</b>  | B   |
| <b>Description of Wiring</b>  |   |
| <b>LED color</b>  | LED red   |
| <b>Suppressor</b>   | diode   |
| <b>Other characteristics</b>  | correct polarity must be ensured                                |
| <b>Technical data</b>   |   |
| <b>Pin dimensions</b>   | 6.3 mm x 0.8 mm   |
| <b>Rated voltage</b>  | DC 24 V   |
| <b>Rated current</b>  | 8 A   |
| <b>Contact resistance</b>   | <= 4 mOhm   |
| <b>Type of termination</b>  | screw / cable shoe / cable eye                                  |
| <b>Suitable cables</b>  | 4.5 mm to 10 mm diameter  |
| <b>Mounting</b>   | central screw   |
| <b>Material</b>   |   |
| <b>Contact surface material</b>   | Sn  |
| <b>Contact bearer material</b>  | PA  |
| <b>Housing material</b>   | PA  |
| <b>Environmental conditions</b>   |   |
| <b>Protection class (IEC 60529)</b>   | IP 65   |
| <b>Pollution severity</b>   | 3   |
| <b>Temperature range</b>  | -40 °C to +90 °C  |
| <b>Inflammability class</b>   |   |
| <b>Housing</b>  | 94 V-1  |
| <b>Contact bearer</b>   | 94 HB   |
| <b>Approvals</b>  |   |
| <b>UR</b>   | in preparation  |
| <b>VDE</b>  | in preparation  |
| <b>Packaging unit</b>   |   |
| <b>Packaging unit</b>   | 50 pieces   |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

Scope of delivery and accessories

Accessories to order separately

(NBR) flat gasket GM 207-3, Order No. 731 423-002; knurled screw GDM 3011-8, Order No. 732 574-001; stainless steel screw GDM 3011 RF-1, Order No. 734 363-001

Picture

Drawing

