


PRÜF 2013

PRÜF 2015

PRÜF 2017

SSK 2002
Test probe set

- with axial socket. It is possible to fit several probe insets into this test probe.

- the Probe insets **PRÜF 2013, PRÜF 2015, PRÜF 2017** and the Tip-protection-head **SSK 2002** is included in the set!

order no. SET 2040 / ..(colour)

- contact parts **nickel-plated**
 - insulation **PA 6.6 (Polyamid)**

colours: see table

description of accessories

Probe inset PRÜF 2013

- both ends of this inset can be used individually. One end has a 5 mm spring loaded steel tip, the other end a rigid steel tip with 4 mm lamella-basket

Probe inset PRÜF 2015

- this inset provides a 2.4 mm lamella-basket plug

Probe inset PRÜF 2017

- this inset provides a 2.4 mm lamella-basket plug

Tip protection head SSK 2002 / .. (colour)

- for IC with 2.5 mm raster (DIL)
 - it can be used as a tool to screw the insets into the probe

| General information | | Technical data | | | | | |
|---------------------------------------------------------------------|--------------|----------------|-----------------------|------------------|---------------|-------------------------------|--|
| order no. | colours | terminal | transition resistance | rated voltage | rated current | Insulation -25 °C ... + 90 °C | |
| | | | | | | operating temperature | |
| SET 2040 / .. (colour) set contact parts nickel-plated | black red | socket | 10 mΩ | 1000 V CAT II | 32 A | - 25 °C ... + 90 °C | |
| PRÜF 2013 spare part contact parts nickel-plated | — | — | 5 mΩ | 1000 V CAT II | 32 A | - 40 °C ... + 110 °C | |
| PRÜF 2015 spare part contact parts nickel-plated | — | — | 5 mΩ | 1000 V CAT II | 12 A | - 40 °C ... + 110 °C | |
| PRÜF 2017 spare part contact parts nickel-plated | — | — | 5 mΩ | 1000 V CAT II | 10 A | - 40 °C ... + 110 °C | |
| SSK 2002 / ..(colour) spare part | black red | — — | — — | — — | — — | - 25 °C ... + 90 °C | |

other colours and platings on request