





Produktinformation
GSSNA 200 schwarz/black
933 110-100

Name	
GSSNA 200 schwarz/black	
	
appliance connector with central nut and 2 screws M 3 x 8	
Lieferinformationen	
Lieferstatus	available
Produktbeschreibung	
Beschreibung	appliance connector with central nut and 2 screws M 3 x 8
Typ	GSSNA 200 schwarz/black
Bestell-Nr.	933 110-100
Polzahl	2 + PE
Norm	DIN EN 175 301-803-C
Gehäusefarbe	schwarz
Bauform	C
Technische Daten	
Bemessungsspannung	AC/DC 250 V
Bemessungsstrom	6 A
Durchgangswiderstand	<= 4 mOhm
Anschlußart	löten
Gehäusebefestigung	schrauben
Werkstoff	
Kontaktflächenmaterial	Sn
Kontaktträgermaterial	PA
Gehäusematerial	PA
Umgebungsbedingungen	
Schutzgrad (IEC 60529)	IP 65
Verschmutzungsgrad	3
Temperaturbereich	-40 °C bis +125 °C
Brennbarkeitsklassen	
Gehäuse	94 HB
Kontaktträger	94 V-2
Zulassungen	
UR	UR
VDE	VDE
SEV	SEV
CSA	CSA
Verpackungseinheit	
Verpackungseinheit	200 Stück
Lieferumfang bzw. Zubehör	
Zubehör gesondert zu bestellen	(NBR) Flachdichtung GSSNA 300-5, Bestell-Nr. 730 232-002; (EPDM) Flachdichtung GSSNA 300-6, Bestell-Nr. 730 365-004

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

Bilder

Zeichnung



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.