



## RS30-1602O6O6SDAEHH

Industrial Networking:Industrial Ethernet:OpenRail System:Compact:Switches 3.0

### Product description

Description	ETHERNET/Fast ETHERNET-switch according to IEEE 802.3 compact, managed, Industrial switch for DIN rail store-and-forward-switching, fanless design, Software Layer 2 Enhanced
Port type and quantity	16 ports in total, 2 Gigabit Ethernet Ports; 1. Uplink Port: Gigabit SFP-Slot; 2. Uplink Port: Gigabit SFP-Slot, 16 standard 10/100 BASE TX, RJ45
Type	RS30-1602O6O6SDAEHH
Order No.	RS30-1602O6O6SDAEHH

### More Interfaces

Power supply/signaling contact	1 x plug-in terminal block, 6-pin
V.24 interface	1 x RJ11 socket
USB interface	1 x to connect auto-configuration adapter ACA21-USB

### Network size - length of cable

Multimode fiber (MM) 50/125 $\mu\text{m}$	cf. SFP module M-SFP-SX/LC and M-SFP-LX/LC
Multimode fiber (MM) 62.5/125 $\mu\text{m}$	cf. SFP module M-SFP-SX/LC and M-SFP-LX/LC
Single mode fiber (SM)9/125 $\mu\text{m}$	cf. SFP module M-SFP-LX/LC
Single mode fiber (LH)9/125 $\mu\text{m}$ (long haul transceiver)	cf. SFP module M-SFP-LH/LC and M-SFP-LX+/LC

### Network size - cascading

Line - / star topology	any
Ring structure (HIPER-Ring)	50 (reconfiguration time < 0.3 sec.)

### Power requirements

Operating voltage	12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V
Current consumption at 24 V DC	516mA
Current consumption at 48 V DC	257mA
Power output in Btu (IT) h	42.4

### Software

Management	Serial interface, web-interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP
Diagnostics	LEDs, log-file, syslog, signal contact, RMON, port mirroring, topology discovery 802.1AB, disable learning
Configuration	Command line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, auto-configuration adapter (ACA21-USB, ACA11 read support)
Security	Port security (IP and MAC), SNMP V3 (no encryption)
Redundancy functions	HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1w, redundant network/ring coupling, dual homing, redundant 24 V power supply
Filter	QoS 4 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), multicast (IGMP snooping/querier), multicast detection unknown multicast, broadcast limiter, fast aging
Industrial Profiles	configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Realtime	SNTP server
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV)

### Ambient conditions

Operating temperature	0° to +60°C
Storage/transport temperature	-40° to +70°C
Relative humidity (non-condensing)	10% to 95%
MTBF	39.6 years

### Mechanical construction



Dimensions (W x H x D)

Mounting DIN rail

Weight 600 g

Protection class IP20

#### Mechanical stability

IEC 60068-2-27 shock 15 g, 11 ms duration, 18 shocks

IEC 60068-2-6 vibration 1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13,2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.

#### EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD) 6 kV contact discharge, 8kV air discharge

EN 61000-4-3 electromagnetic field 10 V/m (80 - 1000 MHz)

EN 61000-4-4 fast transients (burst) 2 kV power line, 1 kV data line

EN 61000-4-5 surge voltage power line: 2kV (line/earth), 1kV (line/line), 1kV data line

EN 61000-4-6 conducted immunity 3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)

#### EMC emitted immunity

FCC CFR47 Part 15 FCC CFR47 Part 15

EN 55022 EN 55022 Class A

#### Approvals

Safety of industrial control equipment cUL 508

Hazardous locations cUL 1604 Class1 Div 2

#### Scope of delivery and accessories

Scope of delivery Device, terminal block, operating manual

Accessories to order separately Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, terminal cable, network management HiVision, auto-configuration adapter (ACA21-USB), 19" installation frame