




**Product information**

**GMNL 209 NJ GB1 LED 24 grau/grey**

<b>Name</b>	
GMNL 209 NJ GB1 LED 24 grau/grey	
	
Bridge-type rectifier with protective circuit (varistor) and function indicator (LED)	
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	Bridge-type rectifier with protective circuit (varistor) and function indicator (LED)
Type	GMNL 209 NJ GB1 LED 24 grau/grey
Order No.	933 400-106
Other standard types	transparent housing, locking screw black: Order No. 933 400-100
Number of contacts	2 + PE
Cable gland	PG 9 (grey)
Cable diameter	6.5 mm
Conductor size	max. 0.75 mm <sup>2</sup>
Standard	DIN EN 175 301-803-B
Housing Color	transparent
Construction type	B
<b>Description of Wiring</b>	
LED color	LED red
Voltage rectifier	bridge-type rectifier
Suppressor	Varistor
<b>Technical data</b>	
Pin dimensions	6.3 mm x 0.8 mm
Rated voltage	AC/DC 24 V
Rated current	2 A (SEV 1011 : 1,5 A) AC / 1 A DC
Contact resistance	<= 4 mOhm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central screw
<b>Material</b>	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
<b>Environmental conditions</b>	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
<b>Inflammability class</b>	
Housing	94 V-1
Contact bearer	94 HB
<b>Approvals</b>	
UR	UR
<b>Packing unit</b>	
Packaging unit	50 pieces

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



**Scope of delivery and accessories**

**Accessories to order separately**

(NBR) flat gasket GMN 209-3, Order No. 733 273-002; knurled screw GDM 3011-8, Order No. 732 574-001; stainless steel screw GDM 3011 RF-1, Order No. 734 363-001

**Picture**

**Drawing**

