




Product information
GMNL 209 NJ LED 24 YE schwarz/black
933 572-100

Name	
GMNL 209 NJ LED 24 YE schwarz/black	
	
function indicator (LED) with freewheeling diode	
Delivery informations	
Availability	available
Product description	
Description	function indicator (LED) with freewheeling diode
Type	GMNL 209 NJ LED 24 YE schwarz/black
Order No.	933 572-100
Other standard types	transparent housing, cable gland grey; Order No. 933 572-106
Number of contacts	2 + PE
Cable gland	PG 9 (black)
Cable diameter	6.5 mm
Conductor size	max. 1.5 mm ²
Standard	DIN EN 175 301-803-B
Housing Color	transparent
Construction type	B
Description of Wiring	
LED color	LED yellow
Technical data	
Pin dimensions	6.3 mm x 0.8 mm
Rated voltage	AC/DC 24 V
Rated current	8 A
Contact resistance	<= 4 mOhm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central screw
Material	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions	
Protection class (IEC 60529)	IP 65
Pollution severity	3
Temperature range	-40 °C to +90 °C
Inflammability class	
Housing	94 V-1
Contact bearer	94 HB
Approvals	
UR	UR
Packing unit	
Packaging unit	50 pieces
Scope of delivery and accessories	
Accessories to order separately	(NBR) flat gasket GMN 209-3, Order No. 733 273-002; knurled screw GDM 3011-8, Order No. 732 574-001; stainless steel screw GDM 3011 RF-1, Order No. 734 363-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

Picture
Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.