



Product information
GDML 2016 LED 48 VR YE grau/grey

Name		GDML 2016 LED 48 VR YE grau/grey
		
		function indicator (LED) with freewheeling diode and protective circuit (varistor)
Delivery informations		
Availability	available	
Product description		
Description	function indicator (LED) with freewheeling diode and protective circuit (varistor)	
Type	GDML 2016 LED 48 VR YE grau/grey	
Order No.	934 421-003	
Other standard types	transparent housing, cable gland black: Order no. 934 421-002	
Number of contacts	2 + PE	
Cable gland	M 16 (grey)	
Conductor size	max. 1.5 mm ²	
Standard	DIN EN 175 301-803-A	
Housing Color	transparent	
Construction type	A	
Description of Wiring		
LED color	LED yellow	
Suppressor	varistor	
Technical data		
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm	
Rated voltage	AC/DC 48 V	
Rated current	8 A	
Contact resistance	<= 4 mOhm	
Type of termination	screw	
Suitable cables	4.5 mm to 10 mm diameter	
Mounting	central nut	
Material		
Contact surface material	Sn	
Contact bearer material	PA	
Housing material	PA	
Environmental conditions		
Protection class (IEC 60529)	IP 65 (gasket necessary)	
Pollution severity	3	
Temperature range	-40 °C to +90 °C	
Inflammability class		
Housing	94 HB	
Contact bearer	94 HB	
Packing unit		
Packaging unit	50 pieces	
Scope of delivery and accessories		
Accessories to order separately	(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-002; knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture
Drawing

