



Product information
EM12H5BFIX Au

Name		EM12H5BFIX Au
		
		Appliance connector for front panel and back-wall mounting with wire ends; front mounting thread M16 x 1,5; screw- / M12 push-pull Fast-Lock; O-Ring included, B-coded
Delivery informations		
Availability		no longer available
Product description		
Description		Appliance connector for front panel and back-wall mounting with wire ends; front mounting thread M16 x 1,5; screw- / M12 push-pull Fast-Lock; O-Ring included, B-coded
Type		EM12H5BFIX Au
Order No.		934 536-211
Type of contact		female
Number of contacts		5
Cable material		PVC
Cable length		0.2 m
Conductor size		0.34 mm ²
Standard		IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2
Housing Color		metallic
Technical data		
Pin dimensions		1 mm
Wire stranding		7 x 0.25 mm
Rated voltage		AC/DC 50 V
Rated current		4 A
Material		
Contact material		Cu Zn
Contact surface material		Au
Contact bearer material		PA
Housing material		Cu Zn/Ni
O-Ring		Viton
Environmental conditions		
Protection class (IEC 60529)		IP 67
Pollution severity		3
Temperature range		-25 °C to +90 °C
Inflammability class		
Contact bearer		94 V-2
Approvals		
UL		UL pending
Packing unit		
Packaging unit		100 pieces
Scope of delivery and accessories		
Accessories to order separately		Fastening nut ELST M M16, Order No. 735 413-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.