



Product information
EF12H4DFIX Au

| | |
|---|---|
| Name | |
| EF12H4DFIX Au | |
|  | |
| Appliance socket for front panel and back-wall mounting with wire ends; front mounting thread M16 x 1.5; screw- / M12 push-pull Fast-Lock; O-Ring included, D-coded | |
| Delivery informations | |
| Availability | no longer available |
| Product description | |
| Description | Appliance socket for front panel and back-wall mounting with wire ends; front mounting thread M16 x 1.5; screw- / M12 push-pull Fast-Lock; O-Ring included, D-coded |
| Type | EF12H4DFIX Au |
| Order No. | 934 537-021 |
| Type of contact | female |
| Number of contacts | 4 |
| Cable material | PVC |
| Cable length | 0.2 m |
| Conductor size | 0.34 mm ² |
| Standard | IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2 |
| Housing Color | metallic |
| Technical data | |
| Wire stranding | 7 x 0.25 mm |
| Rated voltage | AC/DC 250 V |
| Rated current | 4 A |
| Material | |
| Contact material | Cu Zn |
| Contact surface material | Au |
| Contact bearer material | PA |
| Housing material | Cu Zn/Ni |
| O-Ring | Viton |
| Environmental conditions | |
| Protection class (IEC 60529) | IP 67 |
| Pollution severity | 3 |
| Temperature range | -25 °C to +90 °C |
| Inflammability class | |
| Contact bearer | 94 V-2 |
| Approvals | |
| UL | UL pending |
| Packing unit | |
| Packaging unit | 100 pieces |
| Scope of delivery and accessories | |
| Accessories to order separately | Fastening nut ELST M M16, Order No. 735 413-001 |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.