



Product information
EF12HL4DFIX Au

Name	
EF12HL4DFIX Au	
	
Appliance socket for front panel and back-wall mounting with circuit board pins; front mounting thread M16 x 1.5; screw- / M12 push-pull Fast-Lock; O-Ring included; D-coded	
Delivery informations	
Availability	no longer available
Product description	
Description	Appliance socket for front panel and back-wall mounting with circuit board pins; front mounting thread M16 x 1.5; screw- / M12 push-pull Fast-Lock; O-Ring included; D-coded
Type	EF12HL4DFIX Au
Order No.	934 537-022
Type of contact	female
Number of contacts	4
Cable material	PVC
Cable length	0.2 m
Conductor size	0.34 mm ²
Standard	IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2
Housing Color	metallic
Technical data	
Wire stranding	7 x 0.25 mm
Rated voltage	AC/DC 250 V
Rated current	4 A
Material	
Contact material	Cu Zn
Contact surface material	Au
Contact bearer material	PA
Housing material	Cu Zn/Ni
O-Ring	Viton
Environmental conditions	
Protection class (IEC 60529)	IP 67
Pollution severity	3
Temperature range	-25 °C to +90 °C
Inflammability class	
Contact bearer	94 V-2
Approvals	
UL	UL pending
Packing unit	
Packaging unit	100 pieces
Scope of delivery and accessories	
Accessories to order separately	Fastening nut ELST M M16, Order No. 735 413-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.