




**Product information**  
**Configurable Industrial Security-Router -**  
**EagleOne-0200M2M2SDDUY0000HHE05.3.**  
**942 103-005**

<b>Name</b>		<b>Configurable Industrial Security-Router</b>
		
		Industrial firewall and security router with extensive Layer 2 and Layer 3 redundancy features, DIN rail mounted, fanless design.
<b>Delivery informations</b>		
<b>Availability</b>	available	
<b>Product description</b>		
<b>Description</b>	Industrial firewall and security router with extensive Layer 2 and Layer 3 redundancy features, DIN rail mounted, fanless design.	
<b>Port type and quantity</b>	2 ports in total, Ports Fast Ethernet: 2 x 10/100 Mbit/s	
<b>Type</b>	EagleOne-0200M2M2SDDUY0000HHE05.3.	
<b>Order No.</b>	942 103-005	
<b>More Interfaces</b>		
<b>Power supply/signaling contact</b>	1 x plug-in terminal block, 6-pin	
<b>Digital Input</b>	1 x plug-in terminal block, 2-pin	
<b>V.24 interface</b>	1 x RJ11 socket	
<b>USB interface</b>	1 x USB to connect the AutoConfiguration Adapter ACA21-USB EEC	
<b>Network size - length of cable</b>		
<b>Multimode fiber (MM) 50/125 µm</b>	0-5000 m, 8 dB Link Budget bei 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 800 MHz x km 0-5000 m, 8 dB Link Budget bei 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 800 MHz x km	
<b>Multimode fiber (MM) 62.5/125 µm</b>	0-4000 m, 11 dB Link Budget bei 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 500 MHz x km 0-4000 m, 11 dB Link Budget bei 1300 nm, A = 1 dB/km, 3 dB Reserve, B = 500 MHz x km	
<b>Network size - cascading</b>		
<b>Line - / star topology</b>	any	
<b>Power requirements</b>		
<b>Operating voltage</b>	12/24/48 VDC/24 VAC (redundant)	
<b>Power consumption</b>	7.0 W	
<b>Software</b>		
<b>Stateful inspection firewall</b>	Firewall rules (incoming/outgoing, management), DoS prevention, MAC filter, user firewall for external activation of FW rules	
<b>Management</b>	SNMPv3, SSH2/SFTP, HTTPS, V.24 CLI, central user management (RADIUS), SSH1, SNMPv1/2, HiDiscovery, Industrial HiVision, HiView	
<b>Multipoint VPN</b>	Point to point, point to multipoint, remote enable/disable or via digital input, IPsec, IKEv1/v2, 3DES, AES (-128, -192, -256), Pre-Shared Key, X.509v3 certificates, MD5, SHA-1, NAT-T	
<b>Diagnostics</b>	LLDP, LEDs (status, VPN, redundancy, link status, data, ACA), signal contact, logfile, syslog, configuration check	
<b>Configuration</b>	Web based GUI, SNMPv3, CLI, Automatic configuration roll-back, text based configuration file, offline configuration, HiView	
<b>Security</b>	HTTPS, SSHv2, SFTP, SNMPv3, Management VLAN, Role based Access	
<b>Routing</b>	Static routing, multinetting, IP masquerading, 1-to-1 NAT, port forwarding.	
<b>Redundancy functions</b>	Use in redundant networks/ring coupling, firewall redundancy (layer 4)	
<b>Time synchronisation</b>	NTP/SNTP	
<b>Miscellaneous</b>	DHCP Server/Client, DHCP Relay/Option 82, DynDNS, PPP, PPPoE, VLAN-Support, packet capture (pcap Format)	
<b>Ambient conditions</b>		
<b>Operating temperature</b>	0 °C ... 60 °C	
<b>Storage/transport temperature</b>	-40 °C ... 85 °C	
<b>Relative humidity (non-condensing)</b>	10 % ... 95 %	
<b>Mechanical construction</b>		
<b>Dimensions (W x H x D)</b>	60 mm x 145 mm x 125 mm	
<b>Mounting</b>	DIN Rail	
<b>Weight</b>	660 g	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



<b>Protection class</b>	IP20
<b>Approvals</b>	
<b>Basis Standard</b>	CE, FCC, C-Tick, EN61131, EN 60950-1
<b>Safety of information technology equipment</b>	cUL 508
<b>Shipbuilding</b>	Germanischer Lloyd
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Device, terminal blocks, operating instructions, manual on CD
<b>Accessories to order separately</b>	Rail power supply RPS 30, RPS 80 EEC, RPS 120 EEC, terminal cable, network management Industrial HiVision, auto-configuration adapter ACA21-USB EEC, 19" installation frame

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.