

Inserts for M23 circular connectors


EPIC® M23 inserts 17-pin D-Sub ribbon contacts for the M23 circular connector series

Info

for D-Sub ribbon contacts for automated production with crimping machine







EAC



Variety of approval certifications



Robust



Assembly time



Mechanical resistance



Good chemical resistance



Wind Energy



Industrial machinery and plant engineering

Benefits

Efficient assembling thanks to the use of D-Sub contacts-on-reel



Application range

Plant construction

Measurement, control and regulation technology

Apparatus construction

Technical Data

Classification: ETIM 5.0 Class-ID: EC000438

ETIM 5.0 Class-Description: Contact insert for industrial

connectors

Rated voltage (V): according to IEC 61984: 50 V

Rated impulse voltage:

0.8 kV

Rated current in A:

4 A

Pollution degree:

3

Contact resistance: < 4 mOhm

Contacts: Partly gold-plated brass

Number of contacts: 17

Cable connection: Crimp termination: 0.08 – 0.56 mm²

Plug cycles: 50

Temperature range: -25°C to +125°C

Note

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-part and one E-part. P-component = left turning, E-component = right turning

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article description	Inserts	Pin configuration
17-pin inserts, E-part = rotation to the right (clockwise)			
44420128	E-part	Unpopulated, for male D-Sub crimp contact (on reel)	17
44420129	E-part	Unpopulated, for male D-Sub crimp contact (on reel)	17
44420130	E-part	Unpopulated, for female D-Sub crimp contact (on reel)	17
44420131	E-part	Unpopulated, for female D-Sub crimp contact (on reel)	17
17-pin inserts, P-part = rotation to the left (anticlockwise)			
44420132	P-part	Unpopulated, for male D-Sub crimp contact (on reel)	17
44420133	P-part	Unpopulated, for male D-Sub crimp contact (on reel)	17
44420134	P-part	Unpopulated, for female D-Sub crimp contact (on reel)	17
44420135	P-part	Unpopulated, for female D-Sub crimp contact (on reel)	17
	I	. ,	1



